

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product Identifier

Product name: AutoTech 15W-40 Mineral Engine Oil

Product type: Lubricating oil for internal combustion engines

Product description: Petroleum-based lubricating oil with performance additives

Relevant identified uses

Lubrication of petrol and diesel engines

Automotive maintenance and servicing

Uses advised against:

Not for food contact

Not for cosmetic, medical, or pharmaceutical use

Not to be used as a cleaning solvent

Supplier Details

Jivaji Auto Factors Limited

Unit 54, Plume Street Industrial Estate

Birmingham B6 7RT

United Kingdom

Telephone: 0121 687 7768

Email: sales@jivaji.com

Emergency telephone number

Business hours: 0121 687 7768

Outside hours: Contact NHS 111 or local Accident & Emergency Department

SECTION 2: Hazards identification

Classification (GB CLP)

Not classified as hazardous under GB CLP Regulation.

Other hazards

Prolonged or repeated skin contact may cause dermatitis

Used engine oil may contain harmful combustion by-products

Oil spills create slipping hazard

Environmental hazard if released in large quantities

Label Elements

Hazard pictograms: None required

Signal word: None

Hazard statements: Not classified

Precautionary statements

P264 – Wash hands after handling

- P273 – Avoid release to the environment
- P280 – Wear protective gloves during prolonged exposure
- P501 – Dispose of contents/container in accordance with local regulations

SECTION 3: Composition/information on ingredients

Mixture: Fully synthetic lubricating oil

Component	CAS No.	% w/w	Classification
Highly refined mineral base oil	64742-54-7	70-95%	Not classified
Lubricant additives (detergents, dispersants, anti-wear agents, antioxidants)	Proprietary	5-30%	Not classified

No ingredient is present at reportable hazardous levels under CLP.

SECTION 4: First aid measures

General advice

Remove contaminated clothing. Seek medical attention if symptoms persist.

Inhalation

Move person to fresh air.
If breathing difficulty occurs: seek medical attention.

Skin contact

Wash with soap and water.
Remove contaminated clothing.
If irritation occurs ☒ obtain medical advice.

Eye contact

Rinse cautiously with clean water for at least 10 minutes.
Remove contact lenses if present.
Seek medical advice if irritation persists.

Ingestion

Do NOT induce vomiting.
Rinse mouth with water.
Seek medical advice.

Most important symptoms

Mild eye irritation
Skin dryness/dermatitis after prolonged exposure

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Foam
Dry powder
CO2
Water fog

Unsuitable media

Direct water jet

Specific hazards

Combustion may produce carbon monoxide, carbon dioxide, sulphur oxides, phosphorus oxides

Advice for firefighters

Wear self-contained breathing apparatus (SCBA)
Cool containers with water spray
Flash point: >200 °C (typical for engine oils)

SECTION 6: Accidental release measures

Personal precautions

Avoid skin contact
Wear protective gloves
Prevent slipping
Environmental precautions
Prevent entry into drains, soil and watercourses
Containment and clean-up
Contain using sand, earth, or absorbent granules
Collect into suitable labelled container
Dispose via licensed waste contractor

SECTION 7: Handling and storage

Safe handling

Avoid prolonged skin contact
Do not eat, drink or smoke while handling
Wash hands after use
Storage
Store in tightly closed containers
Store between 0°C and 40°C
Keep away from strong oxidising agents

Incompatible materials

Strong oxidisers

SECTION 8: Exposure controls / personal protection

Exposure limits

No specific workplace exposure limit assigned for the mixture.

Oil mist (general guidance): 5 mg/m³ (8-hr TWA typical occupational guidance).

Engineering controls

Provide adequate ventilation where oil mist may form.

Personal protective equipment

Hands: Nitrile gloves

Eyes: Safety glasses if splashing possible

Skin: Protective clothing for prolonged contact

Respiratory: Not normally required

SECTION 9: Physical and chemical properties

Property	Value
Appearance	Amber liquid
Odour	Mild petroleum
pH	Not applicable
Pour point	approx. -24°C
Flash point	>200°C
Auto-ignition temperature	>300°C
Density	~0.87 g/cm ³ @ 15°C
Solubility	Insoluble in water
Viscosity	SAE 15W-40 grade

SECTION 10: Stability and reactivity

Reactivity: Stable under normal conditions

Chemical stability: Stable

Possibility of hazardous reactions: None known

Conditions to avoid: Excessive heat, open flame

Incompatible materials: Strong oxidising agents

Hazardous decomposition products: CO, CO₂, aldehydes, sulphur oxides

SECTION 11: Toxicological information

Acute toxicity

Low toxicity expected.

Likely routes of exposure

Skin contact (primary)

Eye contact

Inhalation of oil mist

Effects

Skin: Dryness/irritation after prolonged exposure

Eyes: Mild irritation
Inhalation: Irritation if mist inhaled
Ingestion: Gastrointestinal discomfort

Used oil may contain carcinogenic combustion contaminants.

SECTION 12: Ecological information

Ecotoxicity: Harmful to aquatic organisms in large quantities
Persistence/degradability: Not readily biodegradable
Bioaccumulative potential: Low to moderate
Mobility in soil: Floats on water, spreads on surface
Other adverse effects: Oil films can reduce oxygen transfer in water

SECTION 13: Disposal considerations

Dispose in accordance with Environmental Protection Act and local authority requirements.

Do not discharge into drains.

Waste code (typical):
13 02 05* – Mineral-based non-chlorinated engine oils

Used oil must be collected by licensed waste oil contractor.

SECTION 14: Transport information

Not classified as dangerous goods for transport.

ADR/RID: Not regulated
IMDG: Not regulated
IATA: Not regulated
UN number: Not applicable
Environmental hazards: Avoid bulk release

SECTION 15: Regulatory information

This product is regulated under:
UK REACH Regulation (EC 1907/2006 retained law)
GB CLP Regulation (classification, labelling and packaging)

Contains highly refined base oils not classified as carcinogenic.

COSHH assessment recommended for workplace use.

SECTION 16: Other information

Key abbreviations

ACEA: European Automobile Manufacturers Association

CI: Low SAPS engine oil category (for vehicles with DPF systems)

SAPS: Sulphated ash, phosphorus and sulphur

TWA: Time-weighted average

Training advice

Users should be trained in safe handling of lubricants and spill response.

Disclaimer

This information is based on available knowledge of lubricating oil mixtures and is intended to describe safety requirements only. It does not constitute a product specification or guarantee of properties.

Revision date: 21/10/2025

Version: 1.4